

	A104 High-Visibility Transit Case for PD Units (6005-0004)		A246 PHD 1-20/2-40/DCCT Test Probe Handle (6005-0420)		E947-E956 Carbon-Coated Circular Electrodes (6005-0242/-0243/-0246) 185mm diameter		A13 Earthing Magnet (6005-0059)				
	A101 PD Range & WRP Battery Charger (6005-0001)		A51 Trimtool for PHD 1-20 and PHD 2-40 (6005-0084)		A110 PD 6 Coiled Interconnecting lead (6005-0008)		A20 PHD 1-20/2-40 Red Carrying Bag (6005-0065)				
	A103 PD 30/40 Coiled Interconnecting Lead (6005-0003)		A38 PD/PHD Trailing Earth Lead (6005-0079)		A105 Screwdriver (6005-0005)		A30 Mains Charger Lead (6005-0077) For PHD 1-20 / 2-40				
	A102 PD Range Battery (D Cell) (6005-0002)		E850, E860 & E870 Roller Electrodes (6005-0231/-0232/-0233) 500mm, 600mm & 700mm available		A50 Test Voltage Calculator (6005-0083)		A29 50m Earth Lead Extension (6005-0076) PD/PHD/DCCT				
	A108 PD 6/30/40kV Red Carry Bag (6005-0041)		A26 5m Earth Lead (6005-0073) PD/PHD/DCCT		A27 10m Earth Lead (6005-0074) PD/PHD/DCCT		A32 Blue Transit Case (6005-0078) For PHD 1-20/2-40				
	A10 Rolling Spring Connectors (6005-0054)		E704-E766 Rolling Spring Electrodes (6005-0201 to 6005-0230) 100mm/4" to 1676mm/66" dia.		A28 25m Earth Lead Extension (6005-0075) PD/PHD/DCCT		A22 Red Transit Case (6005-0066) For PHD 1-20/2-40				
	Insulated Extension Rods (6005-0089/-0273/-0090/-0056/-0057/-0095) A7 220mm A8 330mm A11A 460mm + end cap A7A 220mm + end cap A11 460mm (handle end) A9 1000mm		E960 Twisted-in-Wire Carbon Brush Electrode (6005-0246)		E308-E332 Curved Phosphor Bronze Brush Electrodes (6005-0146 to 6005-0156) 200mm/8" to 800mm/32"		A25 High-Voltage Lead (6005-0071)				
	A12 Rolling Spring Shoe Attachment (6005-0058) Connects Rolling Spring Electrodes (E704 - E748), Phosphor Bronze Electrodes (E104 - E124) or Silicone Rubber Electrodes (E204 - E224) to extension rod.		E408-E432 Curved Silicone Rubber Electrodes (6005-0163 - 6005-0172) 200mm/8" to 800mm/32"								
	E204-E224 Straight Silicone Rubber Electrodes		E104-E124 Straight Phosphor Bronze Electrodes								
E204 100mm/4" 90°	E204A 100mm/4" 45°	E206 150mm/6" 90°	E206A 150mm/6" 45°	E210 250mm/10" 90°	E210A 250mm/10" 45°	E212 300mm/12" 90°	E212A 300mm/12" 45°				
E208 200mm/8" 90°	E208A 200mm/8" 45°	E210 250mm/10" 90°	E210A 250mm/10" 45°	E214 350mm/14" 90°	E214A 350mm/14" 45°	E216 400mm/16" 90°	E216A 400mm/16" 45°				
E212 300mm/12" 90°	E212A 300mm/12" 45°	E214 350mm/14" 90°	E214A 350mm/14" 45°	E218 450mm/18" 90°	E218A 450mm/18" 45°	E220 500mm/20" 90°	E220A 500mm/20" 45°				
E216 400mm/16" 90°	E216A 400mm/16" 45°	E218 450mm/18" 90°	E218A 450mm/18" 45°	E224 600mm/24" 90°	E224A 600mm/24" 45°						
E220 500mm/20" 90°	E220A 500mm/20" 45°										
E334 1200mm/47" 90°	E334A 1200mm/47" 45°										
For details on the full range of silicone rubber electrodes, please see data sheet E2.											
	E104-E124 Straight Phosphor Bronze Electrodes		E106-E124 Straight Phosphor Bronze Electrodes		E106-E124 Straight Phosphor Bronze Electrodes						
E104 100mm/4" 90°	E104A 100mm/4" 45°	E106 150mm/6" 90°	E106A 150mm/6" 45°	E110 250mm/10" 90°	E110A 250mm/10" 45°	E112 300mm/12" 90°	E112A 300mm/12" 45°				
E108 200mm/8" 90°	E108A 200mm/8" 45°	E110 250mm/10" 90°	E110A 250mm/10" 45°	E114 350mm/14" 90°	E114A 350mm/14" 45°	E116 400mm/16" 90°	E116A 400mm/16" 45°				
E112 300mm/12" 90°	E112A 300mm/12" 45°	E114 350mm/14" 90°	E114A 350mm/14" 45°	E118 400mm/18" 90°	E118A 400mm/18" 45°	E120 400mm/20" 90°	E120A 400mm/20" 45°				
E114 350mm/14" 90°	E114A 350mm/14" 45°	E116 400mm/16" 90°	E116A 400mm/16" 45°	E118 400mm/18" 90°	E118A 400mm/18" 45°	E122 500mm/24" 90°	E122A 500mm/24" 45°				
E118 400mm/18" 90°	E118A 400mm/18" 45°	E120 400mm/20" 90°	E120A 400mm/20" 45°								
E120 400mm/20" 90°	E120A 400mm/20" 45°										
For details on the full range of phosphor bronze brush electrodes, please see data sheet E1.											

Note: Due to ongoing technical developments, all stated information is typical and is subject to change without notice or obligation.

AFTER SALES SERVICE / TECHNICAL SUPPORT

All Buckleys products are manufactured under the controls established by a quality management system that meets the requirements of BS EN ISO 9001:2008 and are supplied with a one year 'back-to-base' warranty. The equipment is proven to be robust and reliable and will give years of service if maintained in accordance with our instructions.

Buckleys provide full repair and calibration facilities; offering a fast turn-around service for customers' equipment.

Advice on specific applications for all Buckleys products is available from our technical department. Contact us by telephoning, sending a fax or by e-mail using the contact details below.

Buckleys (UVRAL) Ltd.

Buckleys House, Unit G, Concept Court, Shearway Business Park, Shearway Road, Folkestone, Kent. CT19 4RG. UK

Tel: +44 (0)1303 278888 Fax: +44 (0)1303 274331 Email: sales@buckleys.co.uk Website: www.buckleysinternational.com